

**RAIMOL QBATH
QUENCHING OIL****Identification of the Substance/Preparation and Company Undertaking**

Product Name: RAIMOL QBATH

Product Information: Quenching Oil

Company Name: Rainchem International, Inc.

Address: 4015 Le Cul de Sac Street, Sun Valley, Paranaque City

Phone Number: (632)403-8297

Composition/Information on Ingredients

Chemical Name	CAS Number
Lubricating Base Oil. Could be a mixture of any of the following:	64741895,64741964
Highly Refined Mineral Oil	64742570,64742650
	64742478

Risk Phrases and Symbol

RAI 1 = Irritating to eyes

RAI 2 = Irritating/Harmful to respiratory system

RAI 3 = Irritating to skin

Hazards Identification

Health: Lubricating Oils may cause any skin disease or respiratory illness.

Skin Contact: RAI 3

Eye Contact: RAI 1

Inhalation/Ingestion: RAI 2 (Have no harmful effect in normal temperature and atmospheric pressure).

First-Aid Measures

Skin Contact: Directly contact to the skin! Remove contaminated clothing/shoes. Rinse with water and wash thoroughly with soap. If irritations occur get medical attention promptly to prevent any serious injury.

Eye Contact: Immediately rinse with water for at least 15 minutes. If irritations occur, medical attention is required.

Ingestion: Do not induce Vomiting! In general, no treatment is necessary unless huge quantities of products are ingested, however medical advice is necessary.

Inhalation: Avoid unnecessary actions without the prior attention of the medical team or just simply remove the victim to open area and provide oxygen to avoid any Respiratory failure.

Fire Fighting Measures

FIRE: FIRE CLASSIFICATION: OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible. NFPA

RATINGS: Health: 0 Flammability: 1 Reactivity: 0 FLAMMABLE PROPERTIES: Flashpoint: (Cleveland Open Cup) 176 °C (349 °F) (Min)

Auto ignition: No Data Available Flammability (Explosive) Limits (% by volume in air): Lower: Not Applicable Upper: Not Applicable

FIRE CLASSIFICATION: OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible. NFPA RATINGS: Health: 0 Flammability: 1 Reactivity: 0 FLAMMABLE PROPERTIES: Flashpoint: (Cleveland Open Cup) 176 °C (349 °F) (Min) Auto ignition: No Data Available Flammability (Explosive) Limits (% by volume in air): Lower: Not Applicable Upper: Not Applicable Extinguishing Media: Dry chemical foam
Halogen chemical-carbon dioxide

Accidental Release Measures

Personal Precautions: Wear appropriate personal protective suites/equipment such as helmet with face shield, bunker coats, glove and rubber boots.

Environmental Precautions: Prevent entry into waterways, sewer, basements or confined areas.

Method for Cleaning Up: Isolated hazard area. Keep unnecessary and unprotected personnel from arriving. Recover the liquid if possible. Use non sparking tools and equipment's. Do not use combustible materials, such as sawdust.

Handling and Storage

Handling: Keep in tightly closed container

Storage: Do not store in open or unlabelled containers

Exposure Control/Personal Protection

Engineering Measures: The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Control Measure to Consider

No special requirements under ordinary conditions of use and with adequate ventilation (local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area). Please refer to the ACGIH document, Industrial Ventilation, Manual of Recommended Practices most recent edition, for details.

Respirators: If the exposure limit is exceeded and engineering controls are not feasible, a half face piece particulate respirator (NIOSH type p95 or R95 filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type P100 or R100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. Please note that N filters are not recommended for this material. For emergencies or instances where the exposure levels are not known, use a full-face piece Positive-pressure, air-supplied respirator.

Eye Protection: Safety glasses with the side shields are fully recommended.

Use chemical safety goggles and/or a full-face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Occupational Exposure Limits: Components	Agency	TWA	STEL	CEILING	Notation
Highly Refined Mineral Oil	ACGIH	5 mg/m3	10 mg/m3	-----	-----
Highly Refined Mineral Oil	OSHA Z-1	5 mg/m3	-----	-----	-----

Physical and Chemical Properties

Colour	Minimum:	Light 1.5
	Maximum:	Light 2.5
Odor:		Mild
pH:		Not Applicable
Vapor Pressure:		<0.01 mmHg @ 37.8°C (100°F)
Vapor Density (Air=1):		>1
Physical State:		Liquid
Density kg/li:		0.85
Solubility (water):		Soluble in Hydrocarbons; Insoluble in Water
Viscosity @ 40:	Minimum:	10.0 cst (centistokes)
	Maximum:	15.0 cst (centistokes)

Stability and Reactivity

Hazardous Reactions: Stable under normal temperature and pressure.

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decompositions: Material does not decompose

Toxicology Information

Direct or prolonged skin contact with certain lubricating oils can cause mild skin irritation characterized by drying, crackling or oil acne. Injection under the skin cause a wound in muscle and run into the blood stream cause inflammation, swelling, fever, and systematic effects. Including mild central nervous system depression. Injection of pressurized hydrocarbons can cause severe, permanent tissue damage.

Ecological Information

Environmental Mobility: Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

Environmental Degradability: Expected to be persistent.

Eco-toxicity and bioaccumulation: It has a component that expected to be harmful to aquatic organism. Long term adverse effects to aquatic organisms are possible exposure is maintained.

Disposal Considerations

Product and Contaminated Packaging: Dispose of the Products in accordance with the Local and/or National Regulations.

Transport Information

Not regulated

Regulatory Information

Classification and Labelling Danger Symbol: None

Danger Label: None

Safety Phrases: None

Other Information

This MATERIAL SAFETY DATA SHEET deals with the health and safety information. The product should be used in applications specified in the product 's Technical Data Sheet. For any others uses, exposures should be assessed so that appropriate handling practices and training programs can be established to certify safe workplace operations.