

RAIMOL COMPRO 100

Compressor Oil 100

Product Description

COMPRO 100 High Performance Air Compressor Oils are blended from selected high quality paraffinic base oils and additives that include a special ashless high temperature anti-oxidant which eliminates carbon deposits from air discharge valves.

Application

- Recommended for crankcase and cylinder lubrication of reciprocating air compressors, flooded rotary vane, and screw type air compressor.

Performance Features

- Formulated with a special ashless high temperature anti-oxidant.
- Made from a blend of high quality paraffinic base oils.
- Resists carbon formation on discharge valves and air delivery systems.
- Protect against rust and corrosion
- Anti-wear treated
- Separate readily from water.

Physical and Chemical Properties

Appearance:	Clear
Colour:	Minimum: Light 1.5 Maximum: Light 2.5
Odour:	Mild
Flash Point:	240°C
Pour Point °C:	-21
Density (kg/li):	0.885
Solubility (Water):	Insoluble
Viscosity @40:	Typical: 98.0 cst (centistokes)

Health and Safety

This product will not pose a safety health hazard if used properly and industrial safety practices are observed.

As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact. Take used oil to a government accredited recycler. Do not discharge in the environment. See COMPRO 100 MSDS.

Packaging

18 liter pail and 200 liter drum.

RAIMOL is a trademark of Rainchem International, Inc. Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice. For more information, contact your RAIMOL area distributor or visit www.aimol.com