

### RAIMOL HYDRO T68

Turbine Oil ISO VG 68

#### Product Description

**HYDRO T68** is based on a blend of specially chosen highly refined lubricating oil with selected additives to enhance their rust and oxidation properties.

#### Applications

- Power generation steam turbines
- Industrial steam turbines
- Certain industrial gear units
- High-speed gears
- Certain oil-lubricated bearings

#### Performance Features

- Good thermal and oxidation stability
- Excellent corrosion protection
- Excellent oil / water separation properties
- Good air release characteristics

#### Physical and Chemical Properties

Appearance:	Clear
Odour:	Mild
Color:	<b>Minimum:</b> Light 1.5
	<b>Maximum:</b> Light 2.5
Flash Point:	220 <sup>o</sup> C
Pour Point <sup>o</sup> C:	-12 <sup>o</sup> C
Density (kg/li):	0.870
Solubility (Water):	Insoluble
Viscosity @40:	<b>Typical:</b> 68.0 cst (centistokes)

#### Health and Safety

These products will not pose a safety health hazard if used properly and industrial safety practices are observed. As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact. Take used oil to a recycler. Do not discharge in the environment. See HYDRO T68 MSDS.

#### Packaging

18 liter pail and 200 liter drum.

*RAIMOL is a trademark of Rainchem International, Inc. Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice. For more information, contact your RAIMOL area distributor or visit [www.raimol.com](http://www.raimol.com)*