

**RAIMOL LUBRO M40R**

Marine Diesel Engine Oil SAE 40

**Product Description**

**LUBRO M40R** is marine diesel engine oil especially designed for lubrication of medium and high speed trunk piston engines. It consists of premium quality, high-viscosity mineral base oils and additives for premium service performance.

**Applications**

-For highly rated, medium speed trunk piston marine engines, auxiliary marine engines, geared transmissions, oil lubricated stern tubes, deck machineries and other applications requiring SAE 40 viscosity oil. Available in SAE grades 30, 40, and 50.

**Performance Features**

- Contains high alkaline additives that neutralize combustion acids.
- Exceptional engine cleanliness, excellent detergency.
- High oxidation resistance, longer oil life and greater resistance to oxidative thickening.
- Reduce cylinder and piston ring wear
- Excellent water tolerance.
- Enhanced engine protection.
- Effective protection from rust and corrosion.

**Physical and Chemical Properties**

Physical State:		Liquid
Odour:		Mild
Color:	<b>Minimum:</b>	3.0
	<b>Maximum:</b>	3.5
Flash Point:		240°C
Density (kg/li):		0.870
Water Solubility:		Insoluble
Viscosity @ 40:	<b>Typical:</b>	140.0 cst (centistokes)
Viscosity @ 100:	<b>Typical:</b>	14.5 cst (centistokes)
Viscosity Index:	<b>Typical:</b>	102
Total Base Number (mg KOH/g):		12.0

**Health and Safety**

This product does not pose a health or safety hazard when used in the recommended application and when proper industrial safety practices are observed. As with all industrial oils and lubricants, prolonged contact with skin should be avoided, especially with used oils. Wash skin with soap and water after contact. Take used oil to an authorized government accredited recycler. See LUBRO M MSDS.

**Packaging**

18 liter container and 200 liter drum.

*RAIMOL is a trademark of Rainchem International, Inc. Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice. For more information, contact your RAIMOL area distributor or visit [www.aimol.com](http://www.aimol.com)*