

RAIMOL REFRO 32**Refrigeration Oil 32****Product Description**

REFRO 32 is fully de-waxed, high grade petroleum oil for the lubrication of refrigeration systems at ultra-low temperature conditions. It can be force fed or splashed on the pistons, motors and bearings of the refrigerant compressors.

Performance Features

- **Prevents Corrosion** – scaly build-up suppressed by a strong protective lubricating film.
- Corrosion due to vapor or condensation is also prevented by the bonding film of REFRO 32.
- **Stability** – at exceptionally low temperatures, REFRO 32 maintains its stability without forming waxy or solid deposits.
- **Wear Prevention** – REFRO 32 base oil is modified to withstand wear even under extreme compression conditions.
- **Ice Prevention** – Prevention of ice formation in the system is an added function of REFRO 32 to maintain the fluidity of the oil.

Physical and Chemical Properties

Appearance:	Clear
Odour:	Mild
Color:	Minimum: Light 1.5
	Maximum: Light 2.5
Flash Point:	174 ^o C
Pour Point ^o C:	-48
Density (kg/li):	0.850
Solubility (Water):	Insoluble
Viscosity @40:	Typical: 32.0 cst (centistokes)

Health and Safety

This product will not pose a safety health hazard if used properly and industrial safety practices are observed. As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact.

Take used oil to a recycler. Do not discharge in the environment. See REFRO 32 MSDS.

Packaging

18 liter pail and 200 liter drum.

RAIMOL is a trademark of Rainchem International, Inc. Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice. For more information, contact your RAIMOL area distributor or visit www.raimol.com