

RAIMOL SPIRO 680

Gear Oil 680

Product Description

Gear Oil ISO VG 680 is a high quality manual transmission gear lubricants specially formulated to provide excellent extreme pressure protection for heavy duty service.

Application

- Automotive manual transmissions
- Manual transmission of trucks, busses, and heavy equipment
- Bevel gear and hypoid gear transaxles.
- Industrial gear boxes.

Performance Features

- High thermal stability which helps extend oil life
- Effective corrosion inhibition to help protect gearbox component
- Resistant to thickening
- Extreme pressure additive treated
- Anti-wear additive treated
- Excellent protection from rust, corrosion and oxidation.

Physical and Chemical Properties

Appearance:	Clear
Color:	Minimum: Light 2.5
	Maximum: Light 3.0
Odour:	Mild
Flash Point:	>200°C
Density (kg/li):	0.90
Solubility (Water):	Insoluble
Viscosity @40:	Typical: 680.0 cst (centistokes)

Health and Safety

This product does not pose a health or safety hazard when used in the recommended application and when proper industrial safety practices are observed. As with all industrial oils and lubricants, prolonged contact with skin should be avoided, especially with used oils. Wash skin with soap and water after contact. Take used oil to an authorized government accredited recycler. See SPIRO MSDS.

Packaging

18 liter pail and 200 liter drum.

RAIMOL is a trademark of Rainchem International, Inc. Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice. For more information, contact your RAIMOL area distributor or visit www.raimol.com